



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : H01M 2/22	A1	(11) International Publication Number: WO 92/16025 (43) International Publication Date: 17 September 1992 (17.09.92)
<p>(21) International Application Number: PCT/US92/00909</p> <p>(22) International Filing Date: 6 February 1992 (06.02.92)</p> <p>(30) Priority data: 662,598 1 March 1991 (01.03.91) US</p> <p>(71) Applicant: MOTOROLA, INC. [US/US]; 1303 E. Algonquin Road, Schaumburg, IL 60196 (US).</p> <p>(72) Inventor: MORE, Georgina ; 1241 N.E. 8 Street, #6, Delray Beach, FL 33483 (US).</p> <p>(74) Agents: NICHOLS, Daniel, K. et al.; Motorola, Inc., Intellectual Property Dept., 8000 West Sunrise Blvd., Ft. Lauderdale, FL 33322 (US).</p>		<p>(81) Designated States: AT (European patent), BE (European patent), CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), MC (European patent), NL (European patent), SE (European patent).</p> <p>Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: INTEGRAL SOLID STATE EMBEDDED POWER SUPPLY</p> <div style="text-align: center; margin: 20px 0;"> <p><u>10</u></p> </div> <p>(57) Abstract</p> <p>A battery (10) integrally formed in a substrate (2) comprises a first current collector (4) inlaid in the substrate (2) and further coupled to a first electrode (14), a second current collector (6) coupled to a second electrode (16), and a solid state electrolyte (8) between the first electrode (14) and the second electrode (16).</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	MI	Mali
AU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gabon	MR	Mauritania
BE	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	RO	Romania
CA	Canada	IT	Italy	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland			SN	Senegal
CI	Côte d'Ivoire	KR	Republic of Korea	SU	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lanka	TG	Togo
DE	Germany	LU	Luxembourg	US	United States of America
DK	Denmark	MC	Monaco		
ES	Spain	MG	Madagascar		

INTEGRAL SOLID STATE EMBEDDED POWER SUPPLY

5

Technical Field

This invention relates generally to batteries, and more specifically to a solid state battery inlaid in a product housing or substrate.

10

Background

Power supplies in numerous portable products typically take up a substantial portion of the weight and volume of the portable product as a whole. The trend towards less voluminous and lighter power supplies is ever so evident in the communications industry. Thus, any further development that would decrease the overall weight and size of the power supply while maintaining (or increasing) the same charge capacity and life span of present packaged cell batteries would provide a distinct advantage. Typical batteries, such as nickel cadmium batteries, have at least one Ni-Cd cell. Each cell requires a metal casing enclosing a positive and a negative electrode, electrolyte, metal current collectors, and insulators. The term battery is occasionally used to identify a cell. However, it is more correctly used to identify a group of individual cells assembled in a pack with terminals (for electrical contact) and proper insulation such as a plastic housing for the battery pack containment. All this packaging results in an inefficient use of energy per unit volume of power source.

Today, in order to achieve the appropriate voltage and/ or capacity requirements for portable products such as two-way radios and cellular phones, a string of individual cells (each usually contained in a metal can) is coupled serially or in parallel. The main reason for containment in the cell metal casing is the use of liquid electrolyte. This eliminates the risk of contamination of the portable product equipment from electrolyte leakage. Each

cell's metal can is insulated in thin plastic heat shrink wrap to prevent shorting on contact with each other before insertion into the plastic housing. Each cell is then coupled typically using nickel or nickel plated tabs, and then finally the cell pack is held
5 within a hard plastic housing.

With the advent of solid electrolyte and solid conductive polymer materials, a new foundation for battery technology was laid. Conductive polymer materials are semiconductors in their natural state, but they can become conductive when doped
10 (treated) with electron donor materials, ie., alkali metals, or with electron acceptor materials, ie., I₂, AsF₅, SO₃, HSO₃F. These conductive polymers or plastics have a ring structure with delocalized π bonding electrons which are relatively free to move about the polymer chain structure. Conductive polymers such as
15 polyphenylene, polypyrrole, and polyaniline have been used as electrode materials. Polyaniline and its derivatives, in particular, have become of greater interest because of their higher stability in air and their ease of reproducibility. Some of these polymers can be made into thin flexible films which can be shaped or
20 molded into convenient shapes for design compatibility. In addition to the conductive polymer electrodes, polymer electrolytes have been developed which can also be fabricated in thin plastic sheets. Some examples include polyethyleneoxide (PEO), polyphosphazene, polyether-substituted phosphazene
25 (MEEP), and polypropyleneoxide. A list of conductive polymers under development can be found in *Material Engineering* journal, August 1985 issue, page 35, Table 1.

These solid state batteries have the one drawback of low conductivity at normal or ambient operating temperatures. This
30 limits the current rate capability that can be obtained from the system. However, conductivities in the order of 10^{-4} Ω -cm at room temperatures have been attained in laboratories, which are sufficient for some battery applications such as computer memory back-up and memory cards. Solid polymers made into thin films
35 can provide higher rate capabilities by increasing surface area

significantly. Therefore, voltages and capacities are obtained which widen the range of applications for thin film solid state batteries. In addition to the solid state batteries mentioned, some type of supercapacitors can also be used as power sources.

- 5 Recently, a paper presented by Dr. S.D. Bhakta of the Materials Research Laboratory of SRI International at the Electrochemical Society Meeting in Seattle, Washington, on October 14-19, 1990 disclosed the use of polymeric materials in supercapacitors which could actually function as batteries. Therefore, the use of these
10 emerging technologies to provide an integrated battery built into or as part of an equipment housing would result in smaller overall size, lighter overall weight, and lower fabrication cost of the portable equipment.

15 Summary of the Invention

- Accordingly, a battery integrally formed in a substrate, comprises a first current collector embedded in the substrate and further coupled to a first electrode, a second current collector coupled to a second electrode and a solid state electrolyte
20 between the first electrode and the second electrode.

Brief Description of the Drawings

- FIG. 1 is a cross-sectional view of an integral solid state inlaid battery in accordance with the present invention.
25 FIG. 2 is a perspective view of the battery of FIG. 1.
FIG. 3 is simple perspective view of a radio for use in accordance with the present invention.
FIG. 4 is a cross-sectional view of a group of solid state cells in accordance with the present invention.

30

Detailed Description of the Preferred Embodiment

- Referring to FIG. 1, there is shown a battery 10 having a positive end terminal or current collector 6 and negative end terminal or current collector 4. A current collector, either positive
35 or negative, is inlaid or molded into a member 2 which can be a housing, a flex circuit, a substrate, or any other supporting walls

found in a portable electronic product. The positive current collector 6 is coupled to a positive electrode 16. The positive current collector and positive electrode, in combination, is commonly referred to as the cathode. Likewise, the negative current collector 4 is coupled to a negative electrode 14, and their combination is commonly referred to as the anode. In this embodiment, the negative current collector 4 is inlaid or molded into the member 2, but likewise, if so desired, the positive current collector 6 could be imbedded in member 2. In other words, either the negative or positive current collector is an integral inlaid component of the housing or substrate.

Between the anode and the cathode is a solid electrolyte 8 preferably made from such conductive polymer materials as polyethyleneoxide (PEO), polyphosphazene, polyether-substituted phosphazene (MEEP), or polypropyleneoxide. Coupled between the electrolyte 8 and the positive current collector 6 is a positive electrochemically active material such as a positive electrode 16. Coupled between the electrolyte 8 and the negative current collector 4 is a negative electrochemically active material such as a negative electrode 14. Although FIG. 1 shows only one collector embedded in the member 2, it is within contemplation of the present invention that other portions of the battery 10 (i.e., electrode 14, electrolyte 8, electrode 16, and collector 6) could be embedded within the member 2.

The embodiment of FIG. 1 illustrates one cell, but several cells can be laid in series (as seen in FIG. 4) with as many layers of positive electrode, solid electrolyte, and negative electrode as required for an overall desired battery voltage. Likewise, the inlaid battery, in accordance with the present invention could be configured in a parallel connection to achieve an overall desired battery capacity. A bipolar arrangement with one current collector for one electrode common to two cells could also be configured. The solid electrolyte would provide insulation to separate these connections. Thus, in any of these configurations, the elimination of the outside metallic case of each cell and the elimination of the outer packaging for the overall battery provides a considerable

reduction in volume and weight in a portable product. The result is a high energy density, self-powered portable electronic product. Furthermore, since the electrolyte is in a solid state, no contamination or leakage to the portable product componentry will occur.

Referring to FIG. 4, the embedded battery 50 comprises a first cell 10 as described in reference to FIG. 1, electronically coupled to a second cell 20 in series. The second cell 20 comprises, similar to cell 10, a negative current collector 24 coupled to a negative electrode 34 forming an anode, a positive current collector 26 coupled to a positive electrode 36 forming a cathode, and a solid state electrolyte 28 between the cathode and anode. The cell 10 is separated from cell 20 by an insulation means such as the separator 22. The separator 22 typically comprises of polyethylene or other thin nonconductive material. Finally battery 50 comprises of an intercell connection means such as the connector 17, typically made from an electrically conductive metal such as nickel. As previously mentioned, although a series coupling between cells is described, parallel and bipolar coupling arrangements between cells are within contemplation of the present invention.

Referring to FIG. 2 and FIG. 3., the battery 10 is shown embedded in a radio housing 2. The battery 10, as previously described above, comprises a current collector 6 coupled to an electrode 16, another current collector 4 coupled to an electrode 14, and an electrolyte 8 coupled between electrodes 14 and 16. In this embodiment, the positive current collector 6 is coupled to a conductive pad or contact 9 via a conductive runner 7. Likewise, the negative current collector is coupled to a conductive pad or contact 13 via a conductive runner 11. A portion (5) of the conductive runner 11 (shown in dashed lines) is also embedded in the radio housing 2. FIG. 3 illustrates a typical radio 20 that could be used in conjunction with the present invention. Preferably, the radio 20 includes a housing 22, an antenna 24, and contacts 26 and 28 that would couple with the contacts 9 and 13. Of course, other arrangements having the battery 10 on other

housing walls or in printed circuit boards or flex circuits within the housing 22 is within contemplation of the present invention.

What is claimed is:

Claims

1. A battery integrally formed in a substrate, comprising:
a first current collector embedded in said substrate
and further coupled to a first electrode;
5 a second current collector coupled to a second
electrode; and
a solid state electrolyte between said first electrode
and said second electrode.
- 10 2. The battery of claim 1, wherein said substrate comprises
a flexible circuit carrying substrate.
3. The battery of claim 1, wherein said substrate comprises
a portion of a housing.
- 15 4. The battery of claim 1, wherein said first current collector
is selected from the group consisting of expanded metal, metal
screens, and metal foils, wherein the metal foil is selected from
the group consisting of nickel, copper, aluminum, chromium, and
20 combinations thereof.
5. The battery of claim 1, wherein said second current
collector material is selected from the group consisting of
expanded metal, metal screens, and metal foils, wherein the
25 metal foil is selected from the group consisting of nickel, copper,
aluminum, chromium, and any combinations thereof.
6. The battery of claim 1, wherein said first electrode
material is selected from the group consisting of lithium and
30 lithium alloys, lithiated carbon (lithium ion) compounds, and
doped lithium polymers, wherein the doped lithium polymer is
selected from the group consisting of polyphenylene, polypyrrole,
and polyaniline and their derivatives.

7. The battery of claim 1, wherein said second electrode material is selected from the group consisting of metal chalcogenides, wherein the metal chalcogenide is selected from the group consisting of titanium disulfide, vanadium oxides, doped lithium polymers, and redox polymers.

8. The battery of claim 1, wherein said solid state electrolyte is selected from the group consisting of conductive polymer materials, wherein the conductive polymer material is selected from the group consisting of polyethyleneoxide (PEO), polyphosphazene, polyether-substituted phosphazene (MEEP), and polypropyleneoxide.

9. A laminar battery forming an integral part of a portable electronic product, comprising:
a member of said portable product for receiving said laminar battery;
a group of solid state cells electrically coupled together, each cell comprising an anode, a cathode, and a solid electrolyte between said anode and cathode, said cathode comprising of a first current collector and a positive electrochemically active material, said anode comprising of a second current collector and a negative electrochemically active material, one of said cells being embedded in said member;
insulation means for insulating one cell within said group from another cell within said group; and
intercell connection means for electrically coupling said cells.

10. A radio having a battery integrally formed in a member within the radio, comprising:

a first current collector inlaid in said member and further coupled to a first electrode;


5 a second current collector coupled to a second electrode;

a solid state electrolyte between said first electrode and said second electrode.

1/3

FIG. 1

10



2/3

FIG. 2






FIG. 3



3/3

FIG. 450

INTERNATIONAL SEARCH REPORT

International Application No. PCT/US92/00909

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ³		
According to International Patent Classification (IPC) or to both National Classification and IPC		
IPC (5): F01M 2/22 US CL : 429/127		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁴		
Classification System	Classification Symbols	
U.S.	429/98, 127, 152, 162, 192; 455/347	
Documentation Searched other than Minimum Documentation to the extent that such Documents are included in the Fields Searched ⁶		
III. DOCUMENTS CONSIDERED TO BE RELEVANT ¹⁴		
Category ¹	Citation of Document, ¹⁵ with indication, where appropriate, of the relevant passages ¹⁷	Relevant to Claim No. ¹⁸
A	US, A, 2,523,354 (BUTLER) 26 September 1950, See column 1, lines 1-7 and figure 3.	1-10
A	US, A, 4,822,701 (BALLARD ET AL) 18 April 1989, See column 8, lines 32-54 and figure 3.	1-10
A,P	US, A, 5,019,467 (FUJIWARA) 28 May 1991, See figure 1 and column 2, lines 20-27.	1-10
A,P	US, A, 5,019,468 (MIYABAYASHI) 28 May 1991, See figure 4 and column 2, lines 41-59.	1-10
<p>* Special categories of cited documents:¹⁶</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search ²		Date of Mailing of this International Search Report ²
18 JUNE 1992		13 JUL 1992
International Searching Authority ¹		Signature of Authorized Officer ²⁰
ISA/US		STEPHEN J. KALAFUT

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.